

## **IN THE CLAIMS**

This listing of the claim will replace all prior versions and listings of claim in the present application.

### **Listing of Claims**

1. (currently amended) A system comprising:

a first storage system for storing data,

wherein a host computer performs read and write operations on the data stored in the first storage system; and

a switch apparatus connectable the first storage system,

wherein the first storage system includes a plurality of ports connectable to the switch apparatus,

wherein the switch apparatus comprises:

a first port connectable to the first storage system,

a second port connectable to athe host computer,

a third port connectable to a second storage system for storing data,

wherein said host computer performs read and write operations on the data stored in the second storage system, and

a plurality of processing apparatuses connectable to the first, second and third ports,

wherein the plurality of processing apparatuses convert a first protocol which is used in a first connection between the plurality of ports of the first storage system and the first port of the switch apparatus and which is used in a second connection between the host computer and the second port of the switch apparatus to a second protocol which is used in a third connection between the second storage system and the third port of the switch

apparatus<sub>1</sub> when the switch apparatus transfers data from the first storage system to the second storage system.

2. (original) The system according to claim 1, wherein the switch apparatus converts the second protocol to the first protocol when the switch apparatus transfers data from the second storage system to the first storage system.

3. (original) The system according to claim 2, wherein the first protocol is a SCSI protocol and the second protocol is a fiber channel protocol.

4. (original) The system according to claim 3, wherein the plurality of processing apparatuses of the switch apparatus execute a migration of data from the first storage system to the second storage system via the first port and the third port.

5. (original) The system according to claim 4, wherein the switch apparatus further comprises a memory in which information for converting the first protocol to the second protocol and information for converting the second protocol to the first protocol are stored.

6. (original) The system according to claim 4, wherein the migration is executed while the host computer is access the first storage system.

7. (original) The system according to claim 6, wherein the switch apparatus converts a command for responding to the first protocol to the first storage system, said command being transferred by the host computer, to a command for responding to the second protocol to the second storage system to transfer the converted command to the second storage system.

8. (currently amended) A switch apparatus comprising:

- a first port connectable to a first storage system for storing data, wherein a host computer performs read and write operations on the data stored in the first storage system;
- a second port connectable to a host computer;
- a third port connectable to a second storage system for storing data, wherein said host computer performs read and write operations on the data stored in the second storage system; and
- a plurality of processing apparatuses connectable to the first, second and third ports,

wherein the plurality of processing apparatuses converts a first protocol which is used in a first connection between the plurality of ports of the first storage system and the first port of the switch apparatus and which is used in a second connection between the host computer and the second port of the switch apparatus to a second protocol which is used in a third connection between the second storage system and the third port of the switch

apparatus<sub>1</sub> when the switch apparatus transfers data from the first storage system to the second storage system.

9. (currently amended) The switch apparatus according to claim 58, wherein the switch apparatus converts the second protocol to the first protocol when the switch apparatus transfers data from the second storage system to the first storage system.

10. (original) The switch apparatus according to claim 9, wherein the first protocol is a SCSI protocol and the second protocol is a fiber channel protocol.

11. (original) The switch apparatus according to claim 10, wherein the plurality of processing apparatuses of the switch apparatus execute a migration of data from the first storage system to the second storage system via the first port and the third port.

12. (original) The switch apparatus according to claim 11, wherein the switch apparatus further comprises;

a memory in which information for converting the first protocol to the second protocol and information for converting the second protocol to the first protocol are stored.

13. (original) The switch apparatus according to claim 12, wherein the migration is executed while the host computer is accessing the first storage system.

14. (original) The switch apparatus according to claim 13, wherein the switch apparatus converts a command for responding to the first protocol to the first storage system, said command being transferred by the host computer, to a command for responding to the second protocol to the second storage system to transfer the converted command to the second storage system.

15. (currently amended) A system comprising:  
a first storage system for storing data,  
wherein a host computer performs read and write operations on the data stored in the first storage system;  
a switch apparatus connectable to the first storage system; and  
a second storage system connectable to the switch apparatus, the second storage system stores data,  
wherein said host computer performs read and write operations on the data stored in the second storage system,  
wherein the first storage system includes a plurality of ports connectable to the switch apparatus,  
wherein the second storage system includes a plurality of ports connectable to the switch apparatus,  
wherein the switch apparatus comprises:

a first port connectable to the first storage system,  
a second port connectable to a host computer,  
a third port connectable to a second storage system, and  
a plurality of processing apparatuses connectable to the first, second  
and third ports,

wherein the plurality of processing apparatuses convert a first protocol  
which is used in a first connection between the plurality of ports of the first  
storage system and the first port of the switch apparatus and which is used in  
a second connection between the host computer and the second port of the  
switch apparatus to a second protocol used in a third connection between the  
plurality of ports of the second storage system and the third port of the switch  
apparatus, when the switch apparatus transfers data from the first storage  
system to the second storage system.